



HENAN SPT MACHINERY
EQUIPMENT CO., LTD.

EU standard

**SPT Brand Spider Crane – Benchmarking
the World's Highest Standard**

Intelligent, safe and more durable

SPT199



Model		SPT199
Capacity		2.0t×1.4m
Working radius		5.93m×0.20t
Lifting height		6.60m×0.80t
Underground lifting height		10m-4 fall 20m-2 fall 40m-1 fall
Operate system	Type of operation	Wireless remote control and manual operation
	Operating characteristic	Full proportional control
Dimension	Length×Width×Height	2500mm×650mm×1460mm
Weight	(Without optional equipment)	1650kg
Standard configuration	Diesel engine, Electric motor, Radio remote control, Searcher hook, Black rubber track, Intelligent display screen, Moment limiter, Over hoist alarm and automatic stop device, Three-winding alarm and automatic stop device, Automatic hook stow, Outrigger position detector device, Outrigger off the ground alarm and automatic stop device, Slings rope detachment protector, EMO switch, Three color lamp, Remote control lamp, Voice prompt, Walking/Outrigger/Boom three-mode interlock system, Data records	
Optional configuration	Glass suction, White rubber track, Manual fly jib, Single-man basket, Outrigger pads	

SPT299



Model		SPT299
Capacity		2.95t×1.4m
Working radius		8.83m×0.15t
Lifting height		9.50m×0.70t
Underground lifting height		10m-4 fall 20m-2 fall 40m-1 fall
Operate system	Type of operation	Wireless remote control and manual operation
	Operating characteristic	Full proportional control
Dimension	Length×Width×Height	3500mm×900mm×1610mm
Weight	(Without optional equipment)	2550kg
Standard configuration	Diesel engine, Electric motor, Radio remote control, Searcher hook, Black rubber track, Intelligent display screen, Moment limiter, Over hoist alarm and automatic stop device, Three-winding alarm and automatic stop device, Automatic hook stow, Outrigger position detector device, Outrigger off the ground alarm and automatic stop device, Slings rope detachment protector, EMO switch, Three color lamp, Remote control lamp, Voice prompt, Walking/Outrigger/Boom three-mode interlock system, Data records	
Optional configuration	Glass suction, White rubber track, Manual fly jib, Hydraulic fly jib, Single-man basket, Outrigger pads	

SPT399



Model		SPT399
Capacity		4.0t×2.0m
Working radius		12.2m×0.30t
Lifting height		12.9m×0.90t
Underground lifting height		16m-4 fall 32m-2 fall 64m-1 fall
Operate system	Type of operation	Wireless remote control and Dual axis joystick controller
	Operating characteristic	Full proportional control
Dimension	Length×Width×Height	4350mm×1200mm×1750mm
Weight	(Without optional equipment)	4000kg
Standard configuration	Diesel engine, Electric motor, Radio remote control, Searcher hook, Black rubber track, Intelligent display screen, Moment limiter, Over hoist alarm and automatic stop device, Three-winding alarm and automatic stop device, Automatic hook stow, Outrigger position detector device, Outrigger off the ground alarm and automatic stop device, Slings rope detachment protector, EMO switch, Three color lamp, Remote control lamp, Voice prompt, Walking/Outrigger/Boom three-mode interlock system, Data records	
Optional configuration	Glass suction, White rubber track, Manual fly jib, Hydraulic fly jib, Single-man basket, Outrigger pads	

SPT499



Model	SPT499	
Capacity	5.0t×3.0m	
Working radius	16.50m×0.40t	
Lifting height	17.5M×2.0t	
Underground lifting height	17.5m-4 fall 35m-2 fall 70m-1 fall	
Operate system	Type of operation	Wireless remote control and Dual axis joystick controller
	Operating characteristic	Full proportional control
Dimension	Length×Width×Height	5480mm×1400mm×3000 mm
Weight	(Without optional equipment)	6000kg
Standard configuration	Diesel engine, Electric motor, Radio remote control, Searcher hook, Black rubber track, Intelligent display screen, Moment limiter, Over hoist alarm and automatic stop device, Three-winding alarm and automatic stop device, Automatic hook stow, Outrigger position detector device, Outrigger off the ground alarm and automatic stop device, Slings rope detachment protector, EMO switch, Three color lamp, Remote control lamp, Voice prompt, Walking/Outrigger/Boom three-mode interlock system, Data records	
Optional configuration	Glass suction, White rubber track, Manual fly jib, Hydraulic fly jib, Single-man basket, Outrigger pads	

SPT1009



Model	SPT1009	
Capacity	10.0t×2.5m	
Working radius	19m×0.50t	
Lifting height	20.2m×3.0t	
Underground lifting height	20m-6 fall 30m-4 fall 62m-2 fall 125m-1 fall	
Operate system	Type of operation	Wireless remote control and Dual axis joystick controller
	Operating characteristic	Full proportional control
Dimension	Length×Width×Height	6380mm×1780mm×2550mm
Weight	(Without optional equipment)	11800kg
Standard configuration	Diesel engine, Electric motor, Radio remote control, Searcher hook, Black rubber track, Intelligent display screen, Moment limiter, Over hoist alarm and automatic stop device, Three-winding alarm and automatic stop device, Automatic hook stow, Outrigger position detector device, Outrigger off the ground alarm and automatic stop device, Slings rope detachment protector, EMO switch, Three color lamp, Remote control lamp, Voice prompt, Walking/Outrigger/Boom three-mode interlock system, Data records	
Optional configuration	Glass suction, White rubber track, Manual fly jib, Hydraulic fly jib, Single-man basket, Outrigger pads	

Indoor Construction



Outdoor Construction



Curtain Wall Construction



Substation Construction



Buildings Construction



Part of Overseas Agents



Poland



Korea



Malaysia



Turkey



Israel



Australia



HENAN SPT MACHINERY EQUIPMENT CO., LTD.

SPT—The leader of Industry standard

Add

NO.7, QINGLIANGSI AVENUE, LIANGYUAN DISTRICT,
SHANGQIU, HENAN, CHINA.

Mobile

0086 18838927276(Foreign Trade Dept.)

Email

info@sptcrane.com
